

单列密封深沟球轴承
d 60-65mm

基本尺寸			基本额定负荷		疲劳 负荷 极限 P _u	额定转速		质量	型号		尺寸					挡肩及倒角尺寸				计算系数	
d	D	B	动态 C	静态 C ₀		参考转 速	极限转 速 ¹⁾		两侧 带密封件	一侧 带密封件	d	d ₁ ~	d ₂ ~	D ₂ ~	r _{1,2} 最小	d _a 最小	d _a 最大	D _a 最大	r _a 最大	k _r	f ₀
mm			kN		kN	r/min		kg	-		mm					mm				-	
60	110	22	55.3	36	1.53	13000	4000	0.78	*6212-2RS	*6212-RS1	60	75.5	-	98	1.5	69	-	101	1.5	0.025	14
60	110	22	55.3	36	1.53	13000	6300	0.78	*6212-2Z	*6212-Z	60	75.5	-	98	1.5	69	-	101	1.5	0.025	14
65	120	23	58.5	40.5	1.73	12000	3600	0.99	*6213-2RS	*6213-RS1	65	83.3	-	106	1.5	74	-	111	1.5	0.025	15
65	120	23	58.5	40.5	1.73	12000	6000	0.99	*6213-2Z	*6213-Z	65	83.3	-	106	1.5	74	-	111	1.5	0.025	15
85	150	28	87.1	64	2.5	9000	2800	1.80	*6217-2RS	*6217-RS1	85	106	-	134	2	94	-	141	2	0.025	15
85	150	28	87.1	64	2.5	9000	4500	1.80	*6217-2Z	*6217-Z	85	106	-	134	2	94	-	141	2	0.025	15
90	160	30	101	73.5	2.8	8500	2600	2.15	*6218-2RS	*6218-RS1	90	-	106	143	2	101	105	149	2	0.025	15
90	160	30	101	73.5	2.8	8500	4300	2.15	*6218-2Z	*6218-Z	90	113	-	143	2	101	-	149	2	0.025	15
95	170	32	114	81.5	3	8000	2400	2.60	*6219-2RS	*6219-RS1	95	-	112	151	2.1	106	111	159	2	0.025	14
95	170	32	114	81.5	3	8000	4000	2.60	*6219-2Z	*6219-Z	95	118	-	151	2.1	106	-	159	2	0.025	14
100	180	34	127	93	3.35	7500	2400	3.15	*6220-2RS	*6220-RS1	100	-	118	160	2.1	111	117	169	2	0.025	14
100	180	34	127	93	3.35	7500	3800	3.15	*6220-2Z	*6220-Z	100	125	-	160	2.1	111	-	169	2	0.025	14
105	190	36	140	104	3.65	7000	2200	3.70	*6221-2RS	*6221-RS1	105	-	125	167	2.1	117	124	178	2	0.025	14
105	190	36	140	104	3.65	7000	3600	3.70	*6221-2Z	*6221-Z	105	131	-	167	2.1	117	-	178	2	0.025	14
110	200	38	151	118	4	6700	3400	4.35	*6222-2Z	*6222-Z	110	138	-	177	2.1	122	-	188	2	0.025	14
60	110	28	52.7	36	1.53	13000	4000	0.97	62212-2RS	-	60	75.5	-	98	1.5	69	-	101	1.5	0.025	14
65	120	31	55.9	40.5	1.73	12000	3600	1.25	62213-2RS	-	65	83.3	-	106	1.5	74	-	111	1.5	0.025	15
120	215	40	146	118	3.9	6300	3200	5.15	6224-2Z	6224-Z	120	151	-	189	2.1	132	-	203	2	0.025	14
130	230	40	156	132	4.15	5600	3000	5.80	6226-2Z	6226-Z	130	161	-	203	3	144	-	216	2.5	0.025	15
60	130	46	81.9	52	2.2	11000	3400	2.50	62312-2RS	-	60	81.9	-	112	2.1	72	-	118	2	0.03	13
65	140	48	92.3	60	2.5	10000	3200	3.00	62313-2RS	-	65	88.4	-	121	2.1	77	-	128	2	0.03	13