

基本尺寸			基本额定负荷		疲劳 负荷 极限 F _u	额定转速		质量 轴承+ 紧定套	型号		尺寸						挡肩及倒角尺寸					计算系数			
d	D	B	动态 C	静态 C ₀		参考 转速	极限 转速		kg	轴承	紧定套	d ₁	d ₃	D ₁ ~	B ₁	B ₂	r _{1,2} 最小	d _a 最大	d _b 最小	D _a 最大	B _a 最小	r _a 最大	e	Y ₁	Y ₂
mm			kN		kN	r/min		kg	-		mm						-								
25	72	27	31.2	8.8	0.45	18000	13000	0.61	2306K	H2306	25	45	60.9	38	8	1.1	41	35	65	5	1	0.44	1.4	2.2	1.4
30	80	31	39.7	11.2	0.59	18000	12000	0.84	2307EKTN9	H2307	30	52	68.4	43	9	1.5	46	40	71	5	1.5	0.46	1.35	2.1	1.4
35	90	33	54	16	0.82	14000	10000	1.10	2308EKTN9	H2308	35	58	79.2	46	10	1.5	53	45	81	6	1.5	0.40	1.6	2.4	1.6
40	100	36	63.7	19.3	1	13000	9000	1.40	2309EKTN9	H2309	40	65	87.4	50	11	1.5	60	50	91	6	1.5	0.33	1.9	3	2
45	110	40	63.7	20	1.04	14000	9500	1.90	2310K	H2310	45	70	94.4	55	12	2	65	56	99	6	2	0.43	1.5	2.3	1.6
50	120	43	76.1	24	1.25	11000	7500	2.40	2311K	H2311	50	75	103	59	12.5	2	72	61	109	7	2	0.40	1.6	2.4	1.6
65	160	55	124	43	2.04	7500	5600	5.55	2315K	H2315	65	98	139	73	15	2.1	97	82	148	7	2	0.37	1.7	2.6	1.8
70	170	58	135	49	2.24	7000	5300	7.10	2316K	H2316	70	105	148	78	17	2.1	104	88	158	7	2	0.37	1.7	2.6	1.8
75	180	60	140	51	2.28	6700	4800	8.15	2317K	H2317	75	110	157	82	18	3	111	94	166	8	2.5	0.37	1.7	2.6	1.8
80	190	64	153	57	2.50	6300	4500	9.80	2318KM	H2318	80	120	164	86	18	3	115	100	176	8	2.5	0.37	1.7	2.6	1.8
90	215	73	190	80	3.25	5600	4000	14.0	2320KM	H2320	90	130	186	97	20	3	130	110	201	8	2.5	0.37	1.7	2.6	1.8