

基本尺寸			基本额定负荷		疲劳 负荷 极限 P <sub>e</sub>	额定转速		质量	型号			尺寸								挡肩及倒角尺寸					计算系数				
d	D	B	动态 C	静态 C <sub>0</sub>		参考转 速	极限转 速 <sup>1)</sup>		kg	轴承 带止动环和 一侧带防尘 盖	带止动环和 两侧带防尘 盖	止动环	d	d <sub>1</sub> ~	D <sub>2</sub> ~	D <sub>3</sub>	D <sub>4</sub>	b	f	C	r <sub>1,2</sub> 最小	r <sub>0</sub> 最大	d <sub>s</sub> 最小	D <sub>s</sub> 最大	D <sub>0</sub> 最小	b <sub>s</sub> 最小	C <sub>s</sub> 最大	r <sub>s</sub> 最大	k <sub>r</sub>
mm			kN		kN	r/min		kg	-		mm										mm								-
10	30	9	5.4	2.36	0.1	56000	34000	0.032	*6200-ZNR	*6200-2ZNR	SP30	10	17	24.8	28.17	34.7	1.35	1.12	2.06	0.6	0.4	14.2	25.8	36	1.5	3.18	0.6	0.025	13
12	32	10	7.28	3.1	0.132	50000	32000	0.037	*6201-ZNR	*6201-2ZNR	SP32	12	18.5	27.4	30.15	36.7	1.35	1.12	2.06	0.6	0.4	16.2	27.8	38	1.5	3.18	0.6	0.025	12
15	35	11	8.06	3.75	0.16	43000	28000	0.045	*6202-ZNR	*6202-2ZNR	SP35	15	21.7	30.4	33.17	39.7	1.35	1.12	2.06	0.6	0.4	19.2	30.8	41	1.5	3.18	0.6	0.025	13
17	40	12	9.95	4.75	0.2	38000	24000	0.065	*6203-ZNR	*6203-2ZNR	SP40	17	24.5	35	38.1	44.6	1.35	1.12	2.06	0.6	0.4	21.2	35.8	46	1.5	3.18	0.6	0.025	13
20	47	14	13.5	6.55	0.28	32000	20000	0.11	*6204-ZNR	*6204-2ZNR	SP47	20	28.8	40.6	44.6	52.7	1.35	1.12	2.46	1	0.4	25.6	41.4	54	1.5	3.58	1	0.025	13
25	52	15	14.8	7.8	0.335	28000	18000	0.13	*6205-ZNR	*6205-2ZNR	SP52	25	34.4	46.3	49.73	57.9	1.35	1.12	2.46	1	0.4	30.6	46.4	59	1.5	3.58	1	0.025	14
30	62	16	20.3	11.2	0.475	24000	15000	0.20	*6206-ZNR	*6206-2ZNR	SP62	30	40.4	54.1	59.61	67.7	1.9	1.7	3.28	1	0.6	35.6	56.4	69	2.2	4.98	1	0.025	14
35	72	17	27	15.3	0.655	20000	13000	0.29	*6207-ZNR	*6207-2ZNR	SP72	35	46.9	62.7	68.81	78.6	1.9	1.7	3.28	1	0.6	40.6	66.4	80	2.2	4.98	1	0.025	14
40	80	18	32.5	19	0.8	18000	11000	0.37	*6208-ZNR	*6208-2ZNR	SP80	40	52.6	69.8	76.81	86.6	1.9	1.7	3.28	1.1	0.6	47	73	88	2.2	4.98	1	0.025	14
45	85	19	35.1	21.6	0.915	17000	11000	0.41	*6209-ZNR	*6209-2ZNR	SP85	45	57.6	75.2	81.81	91.6	1.9	1.7	3.28	1.1	0.6	52	78	93	2.2	4.98	1	0.025	14
50	90	20	37.1	23.2	0.98	15000	10000	0.46	*6210-ZNR	*6210-2ZNR	SP90	50	62.5	81.6	86.79	96.5	2.7	2.46	3.28	1.1	0.6	57	83	98	3	5.74	1	0.025	14
55	100	21	46.2	29	1.25	14000	9000	0.61	*6211-ZNR	*6211-2ZNR	SP100	55	69.1	89.4	96.8	106.5	2.7	2.46	3.28	1.5	0.6	64	91	108	3	5.74	1.5	0.025	14
60	110	22	55.3	36	1.53	13000	8000	0.78	*6212-ZNR	*6212-2ZNR	SP110	60	75.5	98	106.81	116.6	2.7	2.46	3.28	1.5	0.6	69	101	118	3	5.74	1.5	0.025	14
65	120	23	58.5	40.5	1.73	12000	7500	0.99	*6213-ZNR	*6213-2ZNR	SP120	65	83.3	106	115.21	129.7	3.1	2.82	4.06	1.5	0.6	74	111	131	3.5	6.88	1.5	0.025	15
65	120	23	58.5	40.5	1.73	12000	7500	0.99	*6213-ZNR	*6213-2ZNR	SP120	65	83.3	106	115.21	129.7	3.1	2.82	4.06	1.5	0.6	74	111	131	3.5	6.88	1.5	0.025	15
70	125	24	63.7	45	1.9	11000	7000	1.05	*6214-ZNR	*6214-2ZNR	SP125	70	87.1	111	120.22	134.7	3.1	2.82	4.06	1.5	0.6	79	116	136	3.5	6.88	1.5	0.025	15
70	125	24	63.7	45	1.9	11000	7000	1.05	*6214-ZNR	*6214-2ZNR	SP125	70	87.1	111	120.22	134.7	3.1	2.82	4.06	1.5	0.6	79	116	136	3.5	6.88	1.5	0.025	15