

基本尺寸			基本额定负荷		疲劳 负荷 极限 F <sub>u</sub>	额定转速		质量 轴承+ 紧定套	型号		尺寸						挡肩及倒角尺寸					计算系数			
d	D	B	动态 C	静态 C <sub>0</sub>		参考 转速	极限 转速		轴承	紧定套	d <sub>1</sub>	d <sub>3</sub>	D <sub>1</sub> ~	B <sub>1</sub>	B <sub>2</sub>	r <sub>1,2</sub> 最小	d <sub>a</sub> 最大	d <sub>b</sub> 最小	D <sub>a</sub> 最大	B <sub>a</sub> 最小	r <sub>a</sub> 最大	e	Y <sub>1</sub>	Y <sub>2</sub>	Y <sub>0</sub>
mm			kN		kN	r/min	kg	-							mm										
20	62	17	19	5.4	0.28	22000	15000	0.33	1305EKT9	H305	20	38	52.5	29	8	1.1	37	28	55	6	1	0.28	2.2	3.5	2.5
25	72	19	22.5	6.8	0.36	19000	13000	0.49	1306EKT9	H306	25	45	60.9	27	8	1.1	44	33	65	6	1	0.25	2.5	3.9	2.5
30	80	21	26.5	8.5	0.43	16000	11000	0.65	1307EKT9	H307	30	52	69.5	35	9	1.5	51	39	71	7	1.5	0.25	2.5	3.9	2.5
35	90	23	33.8	11.2	0.57	14000	9500	0.85	1308EKT9	H308	35	58	81.5	36	10	1.5	61	44	81	6	1.5	0.23	2.7	4.2	2.8
40	100	25	39	13.4	0.70	12000	8500	1.20	1309EKT9	H309	40	65	89.5	39	11	1.5	67	50	91	6	1.5	0.23	2.7	4.2	2.8
45	110	27	43.6	14	0.72	12000	8000	1.45	1310EKT9	H310	45	70	95	42	12	2	70	55	99	6	2	0.24	2.6	4.1	2.8
50	120	29	50.7	18	0.92	11000	7500	1.90	1311EKT9	H311	50	75	104	45	12.5	2	77	60	109	7	2	0.23	2.7	4.2	2.8
60	140	33	65	25.5	1.25	8500	6000	2.85	1313EKT9	H313	60	85	127	50	14	2.1	89	70	128	7	2	0.22	2.9	4.5	2.8
65	160	37	79.3	30	1.43	8000	5600	4.20	1315K	H315	65	98	138	55	15	2.1	104	80	148	7	2	0.22	2.9	4.5	2.8
70	170	39	88.4	33.5	1.50	7500	5300	5.00	1316K	H316	70	105	147	59	17	2.1	109	85	158	7	2	0.22	2.9	4.5	2.8
75	180	41	97.5	38	1.70	7000	4800	6.00	1317K	H317	75	110	155	63	18	3	117	91	166	8	2.5	0.22	2.9	4.5	2.8
80	190	43	117	44	1.93	6700	4500	6.90	1318K	H318	80	120	165	65	18	3	122	96	176	8	2.5	0.22	2.9	4.5	2.8
85	200	45	133	51	2.16	6300	4300	7.90	1319K	H319	85	125	174	68	19	3	127	102	186	8	2.5	0.23	2.7	4.2	2.8
90	215	47	143	57	2.36	6000	4000	9.65	1320K	H320	90	130	185	71	20	3	136	108	201	8	2.5	0.23	2.7	4.2	2.8
100	240	50	163	72	2.75	5300	3600	13.5	1322KM	H322	100	145	206	77	21	3	154	118	226	10	2.5	0.22	2.9	4.5	2.8