

Principal dimensions (mm)			Basic load ratings KN		Pu	Speed ratings rpm		Bearing + Withdrawal sleeves	Designation		Dimensions mm										Abutment and fillet dimensions mm			Value			
d <sub>1</sub>	D	B	dyc Cr	stc Cor		Speed Ratings	Limitin g		Bearing	Withdrawal sleeves	d <sub>1</sub>	d <sub>2</sub> ~	D1 ~	B <sub>1</sub>	B <sub>2</sub> <sup>1)</sup>	G	G <sub>1</sub>	b	k	r <sub>1,2</sub> Min	d <sub>a</sub> Max	Da Max	r <sub>a</sub> Max	e	Y1	Y2	Yo
145	320	108	1460	1760	146	1600	2000	45.5	*22330CCK/W33	AHX2330G	145	188	266	135	140	M160×3	24	16.7	9	4	167	303	3	0.35	1.9	2.9	1.8
150	340	114	1600	1960	160	1500	1900	56.0	*22332CCK/W33	AH2332G	150	200	282	140	146	M170×3	24	16.7	9	4	177	323	3	0.35	1.9	2.9	1.8
160	310	86	1120	1460	132	1900	2600	31.0	*22334CCK/W33	AH3134G	160	203	267	104	109	M180×3	16	16.7	9	4	187	293	3	0.27	2.5	3.7	2.5
160	360	120	1760	2160	176	1400	1800	65.5	*22334CCK/W33	AH2334G	160	213	300	146	152	M180×3	24	16.7	9	4	187	343	3	0.33	2	3	2
170	380	126	2000	2450	193	1300	1700	76.0	*22336CCK/W33	AH2336G	170	224	317	154	160	M190×3	26	22.3	12	4	197	363	3	0.35	1.9	2.9	1.8
180	400	132	2120	2650	208	1200	1600	87.5	*22338CCK/W33	AH2338G	180	236	333	160	167	M200×3	26	22.3	12	5	210	380	4	0.35	1.9	2.9	1.8
190	420	138	2320	2900	224	1200	1500	100	*22340CCK/W33	AH2340	190	248	351	170	177	Tr220×430	22.3	12	5	220	400	4	0.33	2	3	2	
200	460	145	2700	3450	260	1000	1400	130	*22344CCK/W33	AOH2344	200	279	389	181	189	Tr240×430	22.3	12	5	240	440	4	0.31	2.2	3.3	2.2	
220	500	155	3100	4000	290	950	1300	165	*22348CCK/W33	AOH2348	220	303	423	189	197	Tr260×430	22.3	12	5	260	480	4	0.31	2.2	3.3	2.2	
220	500	155	3100	4000	290	950	1300	165	*22348CCK/W33	AOH2348	220	303	423	189	197	Tr260×430	22.3	12	5	260	480	4	0.31	2.2	3.3	2.2	
260	540	165	3550	4550	325	850	1100	205	*22352CCK/W33	AOH2352G	260	328	458	205	213	Tr280×430	22.3	12	6	286	514	5	0.31	2.2	3.3	2.2	
280	580	175	4000	5200	365	800	1100	245	*22356CCK/W33	AOH2356G	280	354	492	212	220	Tr300×430	22.3	12	6	306	554	5	0.30	2.3	3.4	2.2	