

Principal dimensions (mm)			Basic load KN		Pu	Speed ratings rpm		Weight kg	Designation		Dimensions mm				Abutment and fillet mm			Value	
d	D	B	dyc Cr	stc Cor		Speed Ratings	Limitin g Speed ¹⁾		With Seals on Both Sides	With Seals on One Side	d	d1 ~	D2 ~	r _{1,2} Min	d _a Min	Da Max	r _a Max	k _r	fo
mm			kN		kN	r/min		kg	-		mm				mm			-	
70	150	35	111	68	2,75	9500	5000	2,50	*6314-ZZ	*6314-Z	70	95	130	2,1	82	138	2	0,03	13
70	150	35	111	68	2,75	9500	3000	2,50	*6314-2RS1	*6314-RS1	70	95	130	2,1	82	138	2	0,03	13
75	160	37	119	76,5	3	9000	4500	3,00	*6315-ZZ	*6315-Z	75	101	138	2,1	87	148	2	0,03	13
75	160	37	119	76,5	3	9000	2800	3,00	*6315-2RS1	*6315-RS1	75	101	138	2,1	87	148	2	0,03	13
80	170	39	130	86,5	3,25	8500	4300	3,60	*6316-ZZ	*6316-Z	80	108	147	2,1	92	158	2	0,03	13
80	170	39	130	86,5	3,25	8500	2600	3,60	*6316-2RS1	*6316-RS1	80	108	147	2,1	92	158	2	0,03	13